#### TOP:013.7A

March 13, 2015

U.S. Fish and Wildlife Service Marquette Biological Station 3090 Wright Street Marquette, Michigan 49855 U.S.A.

and

U.S. Fish and Wildlife Service Ludington Biological Station 229 South Jebavy Drive Ludington, Michigan 49431 U.S.A.

and

Fisheries and Oceans Canada Sea Lamprey Control Centre 1219 Queen Street East Sault Ste. Marie, Ontario P6A 2E5 Canada

## TECHNICAL OPERATING PROCEDURE

#### PROCEDURE TITLE:

Procedures for the Application of Bayluscide 20% Emulsifiable Concentrate

#### APPLICABILITY:

Procedures apply to applications of Bayluscide 20% Emulsifiable Concentrate (EC).

### PRINCIPLE:

Bayluscide 20% EC is an additive applied with TFM to tributaries of the Great Lakes to reduce the quantity of TFM used.

#### SAMPLE COLLECTION AND PRESERVATION:

Not applicable

## **EQUIPMENT REQUIRED**:

See: IOP:IOP:005.x ((Peristaltic (Masterflex) Pumps))

TOP:021.x (Procedures for Conducting Liquid Chromatographic Analysis for Bayluscide) and

IOP: 015.x (High Performance Liquid Chromatograph)

## POTENTIAL INTERFERENCES:

Bayluscide 20% EC is not applied to streams with pH <7.0 or with high concentrations of suspended solids, particularly colloidal clay.

Formulation and equipment must not contact water.

Specific types of tubing are acceptable for delivery of Bayluscide 20% EC (see Attachment 1).

#### SAFETY:

#### I. Environmental Hazards

When applied according to label directions Bayluscide 20% EC does not harm populations of game fish in treated waters. Bayluscide 20% EC is generally not applied if nontarget organisms are congregated in the application area. Aquatic applications of Bayluscide 20% EC are conducted only by personnel licensed by State and Provincial regulatory agencies as certified pesticide applicators.

#### II. Personal Safety

Bayluscide 20% EC is a restricted use pesticide. Follow pesticide label (Appendix E) and SDS (Appendix F) safety instructions.

#### DISPOSAL:

Completely empty the container. Triple-rinse the empty containers and make unsuitable for further use. Dispose of empty containers in an approved sanitary landfill or offer for recycling.

#### **REAGENTS**:

No reagents required

#### PROCEDURES:

Bayluscide 20% EC is applied as an additive toxicant with TFM. The maximum amount which may be applied is 1.5% by weight (A.I.) of the concentration (A.I.) of TFM in the stream. Bayluscide 20% EC and TFM are often applied simultaneously, but in certain situations the application of Bayluscide 20% EC is started 1-2 hours prior to TFM application to ensure proper concentration. Bayluscide 20% EC can be applied to streams in two scenarios:

## I. Primary application

Bayluscide and TFM are applied simultaneously through separate metering systems (IOP:014.x, IOP:005.x, and IOP:005.xA). Procedures used to apply TFM are outlined in TOP:012.x.

The concentration of Bayluscide active ingredient (niclosamide) is determined and is expressed as a percentage of the concentration of TFM active ingredient or as a concentration in ug/L (parts per billion). Bayluscide is applied in concentrations as great as 1.5% of the concentration of TFM. An application rate (mL/min) is calculated with standardized equations (Appendix J).

The Bayluscide 20% EC and TFM are metered into a perforated sump submerged in the stream. A 120-volt AC pump is used to draw the mixture of lampricides and water from the sump and spread it across the stream through one or more perforated hoses. Electrical power is provided at remote sites by a 120-volt AC portable generator. Adjustments of application rates are made independently for each lampricide.

The concentrations of active ingredient for both TFM and Bayluscide are monitored downstream of the application (TOP:018.x and TOP:021.x). Adjustments to the application rates are made on the basis of the results of these analyses.

## II. Maintenance application

The second method allows the application of Bayluscide 20% EC into an existing lampricide block. This type of application usually is necessary in complex stream systems and in downstream reaches of a system. Treatment generally is limited to a downstream location by logistical concerns; all tributaries cannot receive Bayluscide applications due to limitations on numbers of trained personnel, numbers of pumps, 120 volt AC generators, analytical instruments, and Bayluscide mixing apparatus.

The addition of Bayluscide to a lampricide block increases the toxicity of the block significantly. Bayluscide can be added to an existing lampricide block only if the concentration of TFM in the block is near minimum lethal concentration. Carefully planned timing and concentration is required for all upstream applications to provide a lampricide block of suitable concentration at the Bayluscide application site.

Application pumps and analytical instruments are the same for primary and maintenance applications of Bayluscide (IOP:005.x, IOP:005.xA, and IOP:0015.x). Desired concentrations of Bayluscide are planned on the basis of targeted concentrations of TFM at the application site and the predicted minimum lethal concentration with Bayluscide (Appendix I), but may be changed in response to data from TFM analyses.

R	E	$\mathbf{F}$	R	EN	$\mathbf{I}^{\mathbf{C}}$	ES:

None

This procedure has been reviewed and approved by the undersigned representatives of the U.S. Fish and Wildlife Service and Fisheries and Oceans Canada.

REVIEWED/APPROVED\_ ~

Field Supervisor (U.S.)

DATE 3-≥√-/5

REVIEWED/APPROVED

Division Manager (Canada)

DATE Manh 25/2015

# **ATTACHMENT 1**

# Compatibility of Bayluscide 20% Emulsifiable Concentrate and tubing types available for use with Masterflex pumps

# Acceptable:

Platinum cured silicone
Peroxide cured silicone
Tygon silicone
Tygon extended life silicone
C-flex
Pharmed
Pharmed high pressure
Norprene
Norprene food grade
PTFE

# Not Acceptable:

Tygon LFL Tygon food grade Tygon Lab Tygon Fuel and Lubricant Viton